

EXTERNAL ADJUSTABLE WEATHER-RESISTANT BULLET CAMERA



580 NIGHT
TVL
0.03 NIGHT
LUX

**READY FOR
ROUGH
WEATHER**



- 560 TV line high resolution in Color
- Weather-Resistant
- External Lens Control
- 4~9mm Zoom Lens

BU 5649 Sony Super HAD CCD / 560 TVL / 4~9mm MVF / 12VDC

The BU 5649 bullet camera provides a brilliant color resolution in almost any lighting condition. Thanks to the advanced high quality chip-set. The easy to adjust 4-9mm vari-focal lens can be focused and zoomed without the need to open the case. This makes setup a breeze. The included sun-shield and camera mounting bracket make this a complete package. The BU 5649 is a stylish camera that blends into most office environments with ease.

- 1/3" Sony Super HAD color CCD sensor
- Razor Sharp 560 TV Line High Resolution
- 0.4 Lux (Color) / 0.03 Lux (B&W)
- 12 volts DC power source, 120mA power consumption
- 4~9mm Vari-focal Lens installed (External Focus and Zoom adjustable)
- Weather-Resistant
- Mount bracket included

BU 5649	
Lens	4~9mm Vari-focal Lens
Image Pick-Up Device	Sony 1/3 inch Super HAD CCD
Picture Elements	811(H) x 508(V) 410K pixels
Effective Picture Elements	768(H) x 494(V) 380K pixels
Scanning Area	3.65 (H) x 2.74(V)mm
Scanning System	2 : 1 Interface / 525 Lines / 60 Fields / 30 Frames
Resolution	560 (Color) TV Lines / 580 (B/W) TV Lines
Minimum Illumination	0.4 Lux at F1.2 (Color) / 0.03 Lux at F1.2 (B/W)
Sync. System	Internal Only
Video Output	1.0 Vp-p NTSC Comp.
Electronic Iris	1/60 ~ 1/120,000 sec.
Backlight Compensation	Built-in
IRIS Mode	ESC
AGC	Built-in
White Balance	ATW / AWC
Gamma	r=0.45
S/N Ratio	48dB (AGC Off)
Dimension	1.18" (Ø) x 3.9" (L)
Operating Temp	-10°C ~ 50°C (14°F ~ 122°F)
Power Source	DC 12V / 300mA
Power Consumption	100mA