

**Affordable normal resolution
brick camera with Dual Power
Auto detect feature**

380 DAY TV LINE **420** NIGHT TV LINE

0.8 DAY LUX **0.03** NIGHT LUX



Lens not included

- Sharp Image Quality
- One Of The Most Affordable Solution
- Normal Resolution 380 TV Line In Color
- Day & Night
- Dual Power - 12VDC Or 24VAC Auto Detect

CO TP 3924DN 380(C)/420(B) TVL / 0.8/0.03 Lux /1/3 Sony Super HAD

If you need an inexpensive Day & Night camera. That camera is the TP-3924DN. Day & Night feature will automatically change from day mode to night mode with its internal sensor, giving you optimal color clarity during the day and b/w during the night. The super HAD ccd gives you 380 lines of resolution. With your choice of a 12VDC or 24VAC it can be used in any security system. The TP-3924DN has an internal line lock sync system ensures that multi-camera installs will have a sharp picture. The TP-3924DN can be used in banks, casinos, jewelry stores and etc. Consider the TP-3924DN for your next installation needs. (Lens not included)

- 1/3" Sony Super HAD CCD sensor
- Crystal Clear 380 TV Line (Color) Resolution
- 0.8 Lux at F1.2 (Color)
- 0.03 Lux at F1.2 (B/W)
- Day & Night
- 12 volts DC / 24 volts AC auto detects power source
- Auto Tracing White Balance (ATW or AWC) / Back Light Compensation (BLC) / Auto Gain Control (AGC) / Flickerless Mode (FLON)
- DC iris level control
- DC, Video iris control or Electronic Shutter Control (ESC)
- C or CS mount for lens (c-mount adapter included)

CO TP 3924DN	
Image Pick-up Device	Sony 1/3 Super HAD CCD
Resolution	420 (B/W) / 380 TV (Color) Lines Horizontally
Picture Elements	510(H) x 492(V) 270K Pixels
Effective Picture Elements	500(H) x 582(V) 210K Pixels
Scanning Area	4.9(H) x 3.7(V)mm
Scanning System	2:1 Interlace NTSC Standard 525 Line / 60 Fields / 30 Frames
Video Out	1.0 Vp-p NTSC BNC
Electronic Iris	1/60 ~ 100,000 sec
Sync. System	Internal Only
Minimum Illumination	0.8 Lux at F1.2 (Color) 0.03 Lux at F1.2 (B/W for Day & Night Function)
Backlight Compensation	ON/OFF Selectable
Iris Mode	Selectable S/W ESC / Video Drive / DC Drive
Lens	C/CS Mount Changeable
AGC	ON/OFF Selectable
White Balance	Auto Tracking
Gamma	r=0.45
S/N Ratio	More than 48dB (AGC Off)
Ambient Temp.	-10°C ~ +60°C
Dimension	54(W) x 50(H) x 150(L)mm (without lens)
Power Source	AC 24V : 140mA / DC 12V : 210mA
Power Consumption	2.8W

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only, may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.