

4 WAY VIEW DOME CAMERA



OSD
ON SCREEN DISPLAY

560 DAY TV LINE **580** NIGHT TV LINE

0.4 DAY LUX **0.03** NIGHT LUX

- 4 Way Camera
- A convenient way to cover blind spots over 360°

DO 560QUAD 4 Way Camera / Day & Night / 1/3" Sony Super HAD 560TVL / 3.6mm Fixed Lens

- Cameras are placed to each 4 directions. A convenient way to cover blind spots over 360°
- 1/3" Sony Super HAD Color CCD sensor
- Day and Night Function
- High Resolution : 560 TV Line (Color)
- Low Light Sensitive
- 0.4 (Color) / 0.03 Lux (B&W)
- 12 volts DC / 24 volts AC auto detects power source
- Auto Tracing White Balance (ATW) / Back Light Compensation (BLC) / Auto Gain Control (AGC) / Flickerless Mode (FLON)

DO 560QUAD	
Resolution	560(Color) / 580(B/W) TV Lines Horizontally
Image Pick-up Device	Sony 1/3 inch Super HAD CCD
Picture Elements	811(H) x 508(V) 410K pixels
Effective Picture Elements	768(H) x 494(V) 380K pixels
Scanning Area	3.65(H) x 2.74(V) mm
Scanning System	2:1 Interface / 525 Lines / 60 Fields / 30 Frames
Iris Mode	ESC
Lens	3.6mm Fixed Lens
Minimum Illumination	0.4 Lux at F1.2 (Color) / 0.03 Lux at F1.2 (B&W)
Sync. System	Internal Only
Video Output	1.0 Vp-p Comp. 75Ω x 4 (4 Camera Output)
Electronic Iris	1/60 sec ~ 1/100,000 sec
OSD	Built-in
Backlight Compensation	Low / Middle / High / Off Selectable
Gain Control	Low / Middle / High / Off Selectable
White Balance	ATW / AWC / Manual / Outdoor (1,800K~10,500K)
Day & Night	Auto / On
Gamma	r=0.45
S/N Ratio	50dB (AGC Off, Eight On)
Operating Temp.	14°F ~ 122°F
Power Source	DC 12V
Power Consumption	600mA (Power for 4 Cameras)

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only, may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.