

HIDDEN CAMERA



COVERT OPERATION
CAMERA

380 DAY TV LINE **420** NIGHT TV LINE

0.3 DAY LUX **0.03** NIGHT LUX

- 420 TVL Sharp and Crystal Clear Resolution
- 21" Flexible Thin Mount
- PIN-HOLE LENS

HI H220

Fiber Optic Style Endoscope / 420 TVL / 3.7mm Pinhole Lens / DC 12V

This tiny pinhole camera features fiber optic technology and a SONY 1/4" Color CCD chip. This amazing camera measures only about 3/8" at the tip so you can use it to get into the smallest openings for inspection or surveillance applications. Similar to what law enforcement uses, this camera is perfect for a variety of different applications. Whether you need a covert camera positioned just right or need a hand seeing into that tight spot.

- Fiber Optic Style Endoscope Camera
- Sony 1/4" Color CCD : 420 TV Lines
- Low-Illumination
- Pinhole 3.7mm Lens with Audio
- DC 12V : 120mA
- Lens Type, Cable Length, Audio Optional

HI H220	
Video Signal System	NTSC or PAL
Image Sensor	1/4" Sony Color CCD
Effective Pixels Elements	NTSC 512(H) x 492(V) PAL 512(H) x 582(V)
Resolution	420 TV Lines
Video Output	1.0Vp-p (75 ohm, composite)
Sensitivity	0.1 Lux (CDS On 0.001Lux)
Scanning System	2:1 Interlace
Electronic Shutter speed	NTSC 1/60~1/100,000 sec PAL 1/50~1/100,000sec
White Balance	Auto
Sync. System	Internal
Power Consumption	120mA typ.
Lens	3.7mm Pinhole Lens
Operation Temperature	-10°C ~ 45°C
Dimension (WxHxD)	12mm(W) x 12mm(H) x 21mm(L) W/O Main Board
Weight	Approx. 100g