

## SQUARE CASE HIDDEN CAMERA



**OSD**  
ON SCREEN DISPLAY

EXTERNAL  
OSD CONTROL



**560** DAY TV LINE **520** NIGHT TV LINE

**0.4** DAY LUX **0.03** NIGHT LUX

- 560 TV Line Ultra High Resolution in Color
- OSD (On Screen Display) for Easy Camera Setup
- Day & Night

**SQ 560E** 560 TVL / D&N / 3.6mm Fixed Lens / 12VDC / External OSD Control

The SQ 560E is one of top quality and affordable cameras. The SQ 560E has a small joystick OSD control on closure to make easy access setting up the camera and crystal clear high resolution of 560 TV lines at an impressive 0.03 lux rating with help from its Day & Night function.

- 1/3" Sony Super HAD CCD
- 560 (H) TV Line (Color) / 520 (H) TV Line (B/W)
- 3.6mm Fixed Lens
- External OSD (On Screen Display) Control
- Day & Night
- 0.4 Lux (Color) / 0.03 Lux (B/W)
- DC 12V

	<b>SQ 560E</b>
Image Sensor	1/3" Super HAD Color CCD
Picture elements	811(H) x 508(V) 410K pixels
Effective Pixels	768(H) x 494(V) 380K pixels
Sensing Area	3.65(H) x 2.74(V) mm
Scanning System	2:1 Interface / 525 Lines / 60 Fields / 30 Frames
Day & Night	Yes
Horizontal Resolution	560 (H) TV Line (Color) / 520 (H) TV Line (B/W)
S/N Ratio	More than 48dB
Video Output	1.0Vp-p, 75 Ω
Lens	3.6mm Fixed Lens
Minimum Illumination	0.4 Lux (Color) / 0.03 Lux (B&W)
White Balance	AWB
Shutter Speed	1/60 ~ 1/100,000 Sec. (NTSC)
Gamma Characteristic	0.45
Weight	0.7 lbs
Operational Temperature	-10°C ~ 50°C (14°F~122°F) RH 95% Max
Storage Temperature	-20°C ~ 60°C (14°F~122°F) RH 95% Max
Power	12V DC / ±10%
Power Consumption	150mA