

## IP68 Water-proof Vandal-Resistant Dome Camera

**EASY CAMERA INSTALLATION**  
TWIST & LOCK ON BRACKET

**IP68 Certified**

**420 NIGHT TVL**  
**0.03 NIGHT LUX**

**NEW 3-AXIS DOME DESIGN**

Can yours survive?

Service Video-Out  
3-Axis Easy Angle Adjustment



- DT 272V** 380 TVL / 2.8~12mm Auto-Iris Vari-focal Lens / DC 12V / Water-proof / Vandal-Resistant
- DT 272** 380 TVL / 3.6mm Fixed Lens / DC 12V / Water-proof / Vandal-Resistant

The DT 272 and DT 272V vandal-resistant dome cameras are some of the toughest you'll find anywhere. The poly-carbonated impact resistant dome can withstand repeated blows from a 10-pound hammer and not break. The DT 272 and DT 272V have a crisp 380 TV lines of resolution. The precision of the 3.6mm standard lens for the DT 272 and 2.8~12mm Auto-Iris Vari-focal lens for DT 272V allow you to setup the camera quickly and easily. With fine resolution Sony Super HAD CCD, you'll have a crisp and clean image, even at low light environments. The DT 272 and DT 272V dome cameras work great in department stores, jewelry shops, convenience stores and professional business environments. And it runs on 12VDC power supply.

### 3-AXIS CAMERA CONSTRUCTION

Where most dome cameras are 2-Axis, the 3-Axis feature included in these models also insures that you can maneuver the camera at an angle that would be most beneficial when viewing images from these cameras.

- Complete water-proof Camera (IP68 Rating)
- Twist & Lock Easy Installation
- 3 Axis Construction
- Vandal-Resistant Case with Poly-carbonated Cover
- 1/3" Sony Super HAD color CCD sensor
- Day & Night - Sensitivity is increased during night time
- 380 (H) TV Line (Color) / 420 (H) TV Line (B/W)
- Minimum Illumination - 0.3 Lux (Color) / 0.03 Lux (B&W)
- DC 12V
- 3.6mm Fixed Board Lens Installed <sup>DT 272</sup>
- 2.8~12mm Auto-Iris Vari-focal Lens Installed <sup>DT 272V</sup>

	DT 272V	DT 272
Resolution	380(Color) / 420(B/W) TV Lines Horizontally	
Image Pick-up Device	Sony 1/3 inch Super HAD CCD	
Picture Elements	537(H) x 505(V) 270K pixels	
Effective Picture Elements	510(H) x 492(V) 250K pixels	
Scanning Area	3.65(H) x 2.74(V) mm	
Scanning System	2:1 Interface/ 525 Lines / 60 Fields / 30 Frames	
Iris Mode	DC Iris	ESC
Lens	2.8~12mm Auto-Iris Vari-focal	3.6mm Fixed Lens
Minimum Illumination	0.3 Lux at F1.2 / 0.03 Lux at F1.2	
Sync. System	Internal Only	
Video Output	1.0 Vp-p Comp. 75Ω	
Electronic Iris	1/60 sec ~ 1/100,000 sec	
Backlight Compensation	Built-in	
Gain Control	Built-in	
White Balance	AWB	
Day & Night	Auto	
Gamma	r=0.45	
S/N Ratio	50dB (AGC Off, Eight On)	
Operating Temp.	14F ~ 122F	
Power Source	DC 12V	
Power Consumption	120mA	
Weight	2.4 lbs	
Casing / Dimensions	6.0"(D) x 4.5"(H) Vandal-Resistant Storm Case	