

EXTERNAL ADJUSTABLE WEATHER-RESISTANT BULLET CAMERA



**READY FOR
ROUGH
WEATHER**



- 560 TV line high resolution in Color
- Weather-Resistant
- External Lens Control
- 4~9mm Zoom Lens

BU 5649 Sony Super HAD CCD / 560 TVL / 4~9mm MVF / 12VDC

The BU 5649 bullet camera provides a brilliant color resolution in almost any lighting condition. Thanks to the advanced high quality chip-set. The easy to adjust 4-9mm vari-focal lens can be focused and zoomed without the need to open the case. This makes setup a breeze. The included sun-shield and camera mounting bracket make this a complete package. The BU 5649 is a stylish camera that blends into most office environments with ease.

- 1/3" Sony Super HAD color CCD sensor
- Razor Sharp 560 TV Line High Resolution
- 0.4 Lux (Color) / 0.03 Lux (B&W)
- 12 volts DC power source, 120mA power consumption
- 4~9mm Vari-focal Lens installed (External Focus and Zoom adjustable)
- Weather-Resistant
- Mount bracket included

BU 5649	
Lens	4~9mm Vari-focal Lens
Image Pick-Up Device	Sony 1/3 inch Super HAD CCD
Picture Elements	811(H) x 508(V) 410K pixels
Effective Picture Elements	768(H) x 494(V) 380K pixels
Scanning Area	3.65 (H) x 2.74(V)mm
Scanning System	2 : 1 Interface / 525 Lines / 60 Fields / 30 Frames
Resolution	560 (Color) TV Lines / 580 (B/W) TV Lines
Minimum Illumination	0.4 Lux at F1.2 (Color) / 0.03 Lux at F1.2 (B/W)
Sync. System	Internal Only
Video Output	1.0 Vp-p NTSC Comp.
Electronic Iris	1/60 ~ 1/120,000 sec.
Backlight Compensation	Built-in
IRIS Mode	ESC
AGC	Built-in
White Balance	ATW / AWC
Gamma	r=0.45
S/N Ratio	48dB (AGC Off)
Dimension	1.18" (Ø) x 3.9" (L)
Operating Temp	-10°C ~ 50°C (14°F ~ 122°F)
Power Source	DC 12V / 300mA
Power Consumption	100mA

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only, may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.