

IP68 WATER-PROOF VANDAL-RESISTANT DOME CAMERA



MADE IN KOREA

420 NIGHT TVL
0.03 NIGHT LUX

NEW
3-AXIS
DOME DESIGN

- 3-Axis Easy Angle Adjustment



- DT 272V** 420 TVL / 2.8~12mm Auto-Iris Vari-focal Lens / DC 12V / Water-proof / Vandal-Resistant
- DT 272** 420 TVL / 3.6mm Fixed Lens / DC 12V / Water-proof / Vandal-Resistant

EASY CAMERA INSTALLATION TWIST & LOCK ON BRACKET

The DT 272 and DT 272V vandal-resistant dome cameras are some of the toughest you'll find anywhere. The poly-carbonated impact resistant dome can withstand repeated blows from a 10-pound hammer and not break. The DT 272 and DT 272V have a crisp 420 TV lines of resolution. The precision of the 3.6mm standard lens for the DT 272 and 2.8~12mm Auto-Iris Vari-focal lens for DT 272V allow you to setup the camera quickly and easily. With fine resolution Sony Super HAD CCD, you'll have a crisp and clean image, even at low light environments. The DT 272 and DT 272V dome cameras work great in department stores, jewelry shops, convenience stores and professional business environments. And it runs on 12VDC power supply.

3-AXIS CAMERA CONSTRUCTION

Where most dome cameras are 2-Axis, the 3-Axis feature included in these models also insures that you can maneuver the camera at an angle that would be most beneficial when viewing images from these cameras.

- Complete water-proof Camera (IP68 Rating)
- Twist & Lock Easy Installation
- 3 Axis Construction
- Vandal-Resistant Case with Poly-carbonated Cover
- 1/3" Sony Super HAD color CCD sensor
- Day & Night - Sensitivity is increased during night time
- 380 (H) TV Line (Color) / 420 (H) TV Line (B/W)
- Minimum Illumination - 0.3 Lux (Color) / 0.03 Lux (B&W)
- DC 12V
- 3.6mm Fixed Board Lens Installed ^(DT 272)
- 2.8~12mm Auto-Iris Vari-focal Lens Installed ^(DT 272V)

| | DT 272V | DT 272 |
|----------------------------|--|------------------|
| Resolution | 380(Color) / 420(B/W) TV Lines Horizontally | |
| Image Pick-up Device | Sony 1/3 inch Super HAD CCD | |
| Picture Elements | 537(H) x 505(V) 270K pixels | |
| Effective Picture Elements | 510(H) x 492(V) 250K pixels | |
| Scanning Area | 3.65(H) x 2.74(V) mm | |
| Scanning System | 2:1 Interface/ 525 Lines / 60 Fields / 30 Frames | |
| Iris Mode | DC Iris | ESC |
| Lens | 2.8~12mm Auto-Iris Vari-focal | 3.6mm Fixed Lens |
| Minimum Illumination | 0.3 Lux at F1.2 / 0.03 Lux at F1.2 | |
| Sync. System | Internal Only | |
| Video Output | 1.0 Vp-p Comp. 75Ω | |
| Electronic Iris | 1/60 sec ~1/100,000 sec | |
| Gain Control | Built-in | |
| White Balance | AWB | |
| Day & Night | Auto | |
| Gamma | r=0.45 | |
| S/N Ratio | 50dB (AGC Off, Eight On) | |
| Operating Temp. | 14F ~ 122F | |
| Power Source | DC 12V | |
| Power Consumption | 120mA | |
| Weight | 2.4 lbs | |
| Casing / Dimensions | 6.0"(D) x 4.5"(H) Vandal-Resistant Storm Case | |

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only, may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.